

TruStile is pleased to add 20-minute glass doors to its comprehensive lineup of fire-rated door options, which includes 20- through 90-minute ratings.

With TruStile, you never have to sacrifice style for fire door safety. Virtually all of TruStile's stile and rail panel door configurations are available in up to 90-minute ratings. And now, you have the flexibility to specify glass doors in 20-minute ratings.

Fire-rated glass doors are the perfect solution for offices, conference rooms and lobbies where a 20-minute door is required by code but the look of a glass door is preferred.




Product Highlights


TruStile's 20-minute fire-rated glass doors are built with the same premium construction as TruStile's other stile and rail doors.

- Available to meet Category A and Category B requirements
- Hose stream-approved glass available
- Available with any of TruStile's standard sticking profiles
- Over 120 standard door styles
- Available with arch- or radius-shaped glass
- Custom door styles available
- Maximum glass area over 3,000 square inches


Sample Glass Door Styles



TSL4100



TSL2050



FL103

For more information on TruStile's complete line of fire-rated doors, refer to our fire door product data sheets or visit www.trustile.com.

Available Door Styles

TSL Series	Most TSL door styles
PL Series*	PL100, PL130, PL145, PL146, PL200, PL202, PL220, PL230, PL300, PL330, PL400, PL410
FL Series*	FL100, FL101, FL102, FL103, FL110, FL111, FL112, FL113
Custom	Yes, call your TruStile sales representative to discuss your specific requirements


*Not available for divided lite doors.

Specifications


Thickness	1-3/4" minimum
Maximum Size	Single swing: 4'0" wide x 8'0" high
	Pair: 8'0" wide x 8'0" high
	Double Egress: N/A
Panel Construction	
Flat Panel Thickness	1 1/16" thick minimum
Raised Panel Thickness	5/8" thick tongue
Panel Size	
Minimum Panel Size	MDF Doors: 2-3/4" x 2-3/4"
	Wood Doors: 5" x 5"
Maximum Panel Size	MDF Doors: 36-3/4" x 82-1/2"
	Wood Doors: 32" x 74-1/4"
Stock Dimensions	
Stile Face Width	5" minimum
Top Rail Face Width	5" minimum
Bottom Rail Face Width	8-1/4" minimum
Intermediate Stiles/Rails	3-1/2" minimum

Material	Paint-grade MDF Stain-grade wood
Glazing	Compression fit only
Maximum Visible Area	3,145 sq. inches
Non Hose Stream	1/4" thick clear tempered glass
Hose Stream Approved	3/16" thick ceramic with 3M safety film applied <i>Hose stream-approved glazing must be specified (requires custom quote)</i>
Fire Label	Neutral Pressure Positive Pressure Category A Positive Pressure Category B Also available "stamp only" for TruStile authorized dealers and distributors.


Door Construction



Standard 20-Minute Glass Cross Section



Hose Stream-Approved Glass Cross Section



Typical Partial-Lite Cross Section